


LAMIERE PER COPERTURE ONDULATE



CARATTERISTICHE STATICHE DELLA SEZIONE

Le quote si riferiscono ad un profilo di spessore medio

	n.	32	31	30	29	28	26	24	22	20	18	16
SPESSORE	mm.	0,25	0,28	0,30	0,35	0,40	0,50	0,60	0,80	1,00	1,25	1,50
PESO	Kg./m ² .	2,26	2,52	2,72	3,18	3,64	4,56	5,43	7,24	9,05	11,30	13,57
PESO	Kg./m.	1,96	2,20	2,36	2,75	3,14	3,93	4,71	6,28	7,85	9,81	11,77

Carico max utile uniformemente distribuito in Kg/m² Freccia 1/200L

SPESSORE	L	DISTANZA FRA GLI APPOGGI IN METRI										
		1	1,25	1,5	1,75	2	2,25	2,5	2,75			
	0,5	135	65									
	0,6	160	80									
	0,8	210	105	60								
	1,0	265	130	72								
	1,25	330	165	90	50							
	1,5	400	200	110	60							
	0,5	225	110	65								
	0,6	265	135	75								
	0,8	350	180	100	55							
	1,0	445	225	125	70	50						
	1,25	560	280	160	90	60						
	1,5	670	335	190	105	70	50					
	0,5	260	160	105	75	55						
	0,6	310	200	130	95	70	50					
	0,8	410	265	185	120	100	75	60				
1,0	505	315	215	150	115	85	65	50				
1,25	625	385	275	185	135	105	80	55				
1,5	740	450	320	220	160	115	90	60				